

# BULLOCK

## FLEXIBLE FAN CONNECTOR GENERAL PURPOSE

FABRIC ONLY


### PRODUCT DESCRIPTION

Bullock **general-purpose fabric only** flexible fan connector is ideal for on site flexible fan connector installations where metal strips in addition to the fabric is not required. Applications such as Fume extraction systems, Round exhaust systems or minor repairs to existing flexible connections.




### FEATURES

- **Fabric:** Construction is a heavy duty woven denier polyester 650 T/S tearstop PVC coated tarpaulin material with a weight of 690gsm (+/- 30gsm.)
- **Tensile Strength (AS2001.2.3):** WARP - 3320N. WEFT - 2650N.
- **Tongue Tear (BS3424.5):** WARP - 650N. WEFT - 650N.
- **Flex Cracking (AS141.6):** 400,000 Cycles.
- **Coating Adhesion:** Unable to be delaminated, Abrasion resistant.
- **Cold Crack Temperature (CCT):** -30 Degree C.
- **U.V. Treated:** Yes.
- **Anti-fungicide treated:** Yes.
- **Waterproof:** Yes, Acrylic lacquer coated.
- **Airtight:** Yes.
- **Joining Adhesive:** Use general-purpose PVC type adhesives. For high velocity air systems a washer / rivet / washer reinforcing system should be applied.
- **Colour:** Grey.
- **Roll length:** 25 metres.
- **Fabric Widths:** 150mm, 200mm, 250mm.
- **Accessories:**
  - \* Stainless steel - 9mm x 30m banding
  - \* Nylon duct banding
  - \* Screws and housings
  - \* Tensioning tool with cutter.



**Flexible Duct Banding - Nylon**  
Suit 8" Dia. Duct  
Product Code # 1101 - Carton Quantity 100  
Suit 12" Dia. Duct  
Product Code # 1102 - Carton Quantity 100



**Nylon Duct Band  
Tensioning Tool**  
Product Code # 1100



**Flexible Duct Banding  
Stainless Steel**  
30m x 9mm Roll within Plastic Dispenser  
Product Code # 1112

For further information please contact your local representative. Specifications subject to change without notice

**Australian Owned - Australian Made**



#### BULLOCK MFG P/L

22 Pike Street,  
RYDALMERE NSW 2116  
P:9684 1311 F:9684 2250  
sales@bullockmfg.com.au

#### BULLOCK INDUSTRIES P/L

26 Quindus Street,  
WACOL QLD 4076  
P:3271 2088 F:3271 1892  
reception@bullockqld.com.au

#### BULLOCK SA P/L

1 Commercial Court,  
DRY CREEK SA 5094  
P:8349 7088 F:8349 7066  
scott@bullocksa.com.au

#### BULLOCK VIC P/L

54 Tamard Drive,  
BRAESIDE VIC 3195  
P:9587 5522 F:9587 6622  
admin@bullockvic.net.au

#### BULLOCK WA P/L

34 Industry Street,  
MALAGA WA 6062  
P:9248 1633 F:9248 1733  
reception@bullockwa.com.au

For Further Information  
Please Contact your  
Local Representative or  
Visit our Website.

[www.bullockmfg.com.au](http://www.bullockmfg.com.au)

# BULLOCK



## FLEXIBLE FAN CONNECTOR

FABRIC ONLY

Thermal - Elevated Temperature Applications

### PRODUCT DESCRIPTION

Bullock Thermal flexible fan connector fabric only is ideal for on site flexible fan connector installations where metal strips in addition to the fabric is not required.

Applications such as Fume extraction systems, Round exhaust systems or minor repairs to existing flexible connections.



### FEATURES

- **Fabric** yarn construction is Type E glass fibre continuous filament. The weave pattern is a 4 shaft satin design. The fabric thickness is a nominal 0.46mm with a weight of 543gsm. The fabric finish is silicone coated giving the fabric excellent features and benefits.
- **AWTA TEST** number to **AS 1530.3 # 7-441673-BN**. Dated- 25/08/92.  
**Results** : Ignitability Index **0**. Range 0 20. Spread of Flame Index **0**. Range 0 10. Heat Evolved Index **0**. Range 0 10. Smoke Developed Index **1**. Range 0 10.
- **Continuous operating temperatures**:  
Base fabric 550 Degree Celsius. Surface coating 230 Degree Celsius.
- **Joining Adhesive**: High temperature cure silicone equivalent to Rhodorsil RTV-922. For high velocity applications a standard washer / rivet / washer reinforcement may be required.
- **Tensile Strength** (fed 191/5102): WARP - 200kg/50mm. WEFT - 150kg/50mm.
- **Tongue Tear** (fed 191/5136): WARP - 45kg/50mm. WEFT - 30kg/50mm.
- **Coating Adhesion**: (AS1441.5)  
90N / 50mm strip.
- **Chemical Resistance**: Resists most acids, alkalis, and oils.
- **Burst Strength**: 550 p.s.i. (3800 kPa)
- **U.V. Treated**: Yes. Ozone resistant.
- **Anti-fungicide resistant**: Yes.
- **Waterproof**: Yes.
- **Airtight**: Yes.
- **Colour**: Silver.
- **Roll length**: 25 metres.
- **Roll Widths**: 150mm, 200mm, 250mm.
- **Accessories**: \* Stainless steel 9mm x 30m banding.  
\* Screws and housings.



Stainless Steel Banding  
within Plastic Dispenser  
Product Code # 1112

#### BULLOCK MFG P/L

22 Pike Street,  
RYDALMERE NSW 2116  
**P:9684 1311 F:9684 2250**  
sales@bullockmfg.com.au

#### BULLOCK INDUSTRIES P/L

26 Quindus Street  
WACOL QLD 4012  
**P:3271 2088 F:3271 1892**  
reception@bullockqld.com.au

#### BULLOCK SA P/L

1 Commercial Court,  
DRY CREEK SA 5094  
**P:8349 7088 F:8349 7066**  
scott@bullocksa.com.au

#### BULLOCK VIC P/L

54 Tarnard Drive,  
BRAESIDE VIC 3195  
**P:9587 5522 F:9587 6622**  
admin@bullockvic.net.au

#### BULLOCK WA P/L

34 Industry Street,  
MALAGA WA 6062  
**P:9248 1633 F:9248 1733**  
reception@bullockwa.com.au

For Further Information  
Please Contact your  
Local Representative or  
Visit our Website.

[www.bullockmfg.com.au](http://www.bullockmfg.com.au)